



Lightweight concrete screws 10 pcs. 8x100 mm

E-no — MP-no 889E10

Screw 8x100 mm for installation in lightweight concrete with round pan head (Torx TX 40). Supplied with washer \varnothing 18 mm. Screwed directly into lightweight concrete, Leca blocks or the like without pre-drilling. Pull-out value \geq 2 kN. 10 per package.

Product details

E-no

MP-no

EAN

889E10

7394333171401

Dimensions (dxwxh)

Weight kg

Diameter

110x12x12

0.02

12

Surface

Environment class

Electro-galvanized 10 µm

C1



Multi-Monti betongskruv

Multi-Monti är ett koncept med innovativa och smarta betongskruvar, som på ett naturligt sätt kompletterar våra övriga produkter.

Nedanstående måttstablar gäller för espresskruv betong K 25 med säkerhetsfaktor 3. För betong K 20 beräknas 75 % av måttstablen.

| Skruvdimension | Max draglast | Max tvärlast | Borr-hål | Borr-djup | Min kantavstånd | Nyckelvidd |
|----------------|--------------|--------------|----------|-----------|-----------------|------------|
| Ø7,5x50 | 2,7kN | 2,7kN | 6 | 55 | 70 | 10 |
| Ø7,5x55 | 2,9kN | 4,0kN | 6 | 65 | 80 | 10 |
| Ø7,5x70 | 5,9kN | 5,9kN | 6 | 80 | 100 | 10 |
| Ø7,5x75 | 6,3kN | 6,3kN | 8 | 80 | 100 | 13 |

Multi-Monti concrete screws

Multi-Monti is a concept with innovative and smart concrete screws that complement our other products.

The maximum loads below apply to uncracked concrete K25 with a safety factor of 3. For concrete K20 calculate 75% of the maximum loads.

| Screw-size | Max tensile load | Max axial load | Drill-hole | Drill-depth | Min edge distance | Spanner-size |
|------------|------------------|----------------|------------|-------------|-------------------|--------------|
| Ø7,5x50 | 2,7kN | 2,7kN | 6 | 55 | 70 | 10 |
| Ø7,5x55 | 2,9kN | 4,0kN | 6 | 65 | 80 | 10 |
| Ø7,5x70 | 5,9kN | 5,9kN | 6 | 80 | 100 | 10 |
| Ø7,5x75 | 6,3kN | 6,3kN | 8 | 80 | 100 | 13 |

