



Betongskruv 100 st 7,5x50 mm (Borr $\varnothing=6$ mm)

E-nr 1556620 — MP-nr 890E

Betongskruv med fläns som ej kräver plugg. Borra, blås rent och skruva i betongskruven.
Nyckelvidd: 10 mm. Borr: $\varnothing=6$ mm.

Produktdetaljer

E-nr

1556620

Dimensioner (lxbxh)

58x17x17

Ytbehandling

Elförzinkad 10 µm

MP-nr

890E

Vikt kg

0.02

Max miljöklass

C1

EAN

7394333152103

Diameter

17

Förpackning antal

10



Multi-Monti betongskruv

Multi-Monti är ett koncept med innovativa och smarta betongskruvar, som på ett naturligt sätt kompletterar våra övriga produkter.

Nedanstående måttstabell gäller för espresskruv betong K 25 med säkerhetsfaktor 3. För betong K 20 beräknas 75 % av måttstabellen.

Skruvdimension	Max draglast	Max tvärlast	Borr-hål	Borr-djup	Min kantavstånd	Nyckelvidd
Ø7,5x60	2,7kN	2,7kN	6	55	70	10
Ø7,5x55	2,7kN	4,0kN	6	65	80	10
Ø7,5x70	5,9kN	5,9kN	6	80	100	10
Ø7,5x75	6,1kN	6,1kN	8	80	100	13

Multi-Monti concrete screws

Multi-Monti is a concept with innovative and smart concrete screws that complement our other products.

The maximum loads below apply to uncracked concrete K25 with a safety factor of 3. For concrete K20 calculate 75% of the maximum loads.

Screw-size	Max tensile load	Max axial load	Drill-hole	Drill-depth	Min edge distance	Spanner-size
Ø7,5x60	2,7kN	2,7kN	6	55	70	10
Ø7,5x55	2,7kN	4,0kN	6	65	80	10
Ø7,5x70	5,9kN	5,9kN	6	80	100	10
Ø7,5x75	6,1kN	6,1kN	8	80	100	13

