



Betongskruv 50 st 10x70 mm (Borr $\varnothing=8$ mm)

E-nr 1556625 — MP-nr 892Z

Betongskruv med fläns som ej kräver plugg. Borra, blås rent och skruva i betongskruven.
Nyckelvidd: 13 mm. Borr: $\varnothing=8$ mm.

Produktdetaljer

E-nr

1556625

Dimensioner (lxbxh)

78x19x19

Ytbehandling

Varmförzinkad 60 µm

MP-nr

892Z

Vikt kg

0.03

Max miljöklass

C4

EAN

7394333152653

Diameter

19

Förpackning antal

12



Multi-Monti betongskruv

Multi-Monti är ett koncept med innovativa och smarta betongskruvar, som på ett naturligt sätt kompletterar våra övriga produkter.

Nedanstående maxlastar gäller för espresskruv betong K 25 med säkerhetsfaktor 3. För betong K 20 beräknas 75 % av maxlasterna.

Skruvdimension	Max draglast	Max tvärlast	Borr-hål	Borr-djup	Min kantavstånd	Nyckelvidd
Ø7,5x60	2,7kN	2,7kN	6	55	70	10
Ø7,5x55	2,7kN	2,7kN	6	65	80	10
Ø7,5x70	5,9kN	5,9kN	6	80	100	10
Ø7,5x75	6,1kN	6,1kN	8	80	100	13

Multi-Monti concrete screws

Multi-Monti is a concept with innovative and smart concrete screws that complement our other products.

The maximum loads below apply to uncracked concrete K25 with a safety factor of 3. For concrete K20 calculate 75% of the maximum loads.

Screw-size	Max tensile load	Max axial load	Drill-hole	Drill-depth	Min edge distance	Spanner-size
Ø7,5x60	2,7kN	2,7kN	6	55	70	10
Ø7,5x55	2,7kN	2,7kN	6	65	80	10
Ø7,5x70	5,9kN	5,9kN	6	80	100	10
Ø7,5x75	6,1kN	6,1kN	8	80	100	13

